

General Purpose Oil : White Mineral Oil

Product Features

- Colorless. Tasteless. Saturated hydrocarbon compound is highly purified, odorless. The low UV absorbance.
- Chemically stable, inert, non-polar hydrocarbon compound.
- Low volatility, low pour point. Excellent lubricity and insulation and so on.

Product Applications

- Lubricants and petrochemical applications, textile emulsion, coating inspection, materials such as printing inks.
- Wood-preserved, water repellent. Fertilizer industry anti-caking agent.
- Food additives, pharmaceuticals, cosmetics, drug control (emulsion), raw material for agricultural chemicals such as Spray Oil.
- Natural rubber, synthetic rubber, special rubber-extender, blended oil.
- Master Batch - Additive (additive). PP, PE - diluents, plasticizers, extender.
- Food manufacturing machinery lubricants, tableware - microwave food packaging. Food manufacturing anti-foaming agent. Fermentation surface Sealing Layer. Fruits, vegetables, Coating Oils, Meat absorption inhibitors such as packaging, such as an egg.
- Bread and flavor release agent Kim maker, paper inhalation agents, Aluminium Foil - Drawing Stamping lubricant.

General Purpose Oil : White Mineral Oil

Separation	Specific Gravity 15/4°C	Kinematic Viscosity cSt 40 °C	Flash Point °C	Viscosity Index	Pour Point °C
HP-080	0.875	7.85	≥180	78	-25.0
HS-080	0.864	8.56	≥158	60	-35.0
HS-320	0.861	29.5	≥220	101	-15.0
HS-680	0.875	70.5	≥251	110	-15.0
HS-960	0.876	96.5	≥238	98	-20.0
HU-S20	0.820	7.12	≥158	109	-37.5
HU-S30	0.827	13.47	≥204	117	-25.0
HU-S40	0.834	19.62	≥228	123	-20.0
HU-S60	0.841	28.72	≥232	128	-17.5
HU-S80	0.847	43.89	≥256	127	-15.0
HY-L30	0.832	12.73	≥190	105	-45.0
HY-030	0.830	12.43	≥204	112	-24.0
HY-040	0.834	19.57	≥230	122	-15.0
HY-060	0.842	36.82	≥240	131	-15.0
HY-080	0.850	47.3	≥260	128	-12.0